



1 Poles:2P/3P-24P  
 Pitch:7.62mm  
 Voltage Rating:300V  
 Current Rating:25A  
 Wire range:26-12AWG  
 Housing:PA66(UL 94V-0)  
 Wire cage:Steel .Zinc.Plated or Brass  
 Ni Plated  
 Pin header:Brass,Tin Plated  
 Screw:M3,Steel(Q235),Zinc Plated  
 Torque:0.5N.m

序号/RevNO	名称/Title	文件编号/FileNO
1	MG129-7.62塑件	
2	MG129-7.62一字螺丝	
3	MG129-7.62夹子	
4	MG129-7.62方块	

pitch range in mm			Nominal dimension range in mm					—
to	over	over	to	over	over	over	over	
6	10	24	30	60	100	150		
± 0.10	± 0.15	± 0.25	± 0.20	± 0.30	± 0.50	± 0.7	± 1.0	0.05/10

设计/Designed by.	绘图/Drawing by.	审核/Checked by.	批准/Approved by.	未注公差 General Tolerance	
图名/Title		文件编号/FileNO		慈溪市美感电子接插件厂 Cixi Meigan Electric Appliance Socket Factory	X <sup>o</sup> ± 2° .X ± 0.3    .X <sup>o</sup> ± 1° .XX ± 0.15    .XX <sup>o</sup> ± 0.5°
MG129-7.62		页序/Sheet			
备注/Remark	视图/PROJECTION			单位/Units:mm	